


## ECROUS NOYES RIVKLE®


### CYLINDRIQUE MOLETE /ACIER

	Tête	Fût	M3	M4	M5	M6	M8	M10	M12	
	Fine	Ouvert ou Borgne	0.5 – 2.0	0.5 – 3.0	0.5 – 3.0	0.5 – 3.0	0.5 – 3.0	0.5 – 3.0	0.7 – 3.5	
			1.5 - 3.0	2.5 - 4.0	2.5 - 4.0	3.0 – 4.5	3.0 – 4.5	3.0 – 4.5	3.0 – 4.5	3.0 – 4.5
						4.5 – 6.0	4.5 – 6.0	4.5 – 6.0	4.5 – 6.0	


#### Epaisseur à sertir mm

	Plate	Ouvert ou Borgne	0.75 – 1.0	0.5 – 3.0	0.5 – 3.0	0.5 – 3.0	0.5 – 3.0	0.5 – 3.0	0.7 – 3.5	
			1.0 – 1.75	2.5 – 3.25	3.0 – 4.0	3.0 – 5.5	3.0 – 5.5	3.0 – 5.5	3.0 – 4.5	
			1.75 – 2.5						4.5 – 6.0	
			2.5 – 3.25							


#### Epaisseur à sertir mm

	Fraisée	Ouvert ou Borgne	1.0 – 1.75	1.0 – 1.75	1.0 – 2.0	1.5 – 3.0	1.5 – 3.0	1.5 - 3.0		
			1.75 – 2.5	1.75 – 2.5	2.0 – 3.0	3.0 – 4.5	3.0 – 4.5	3.0 – 4.5	3.0 – 4.5	
			2.5 – 3.25	2.5 – 3.25	3.0 – 4.0	4.5 – 6.0	4.5 – 6.0	4.5 – 6.0	4.5 – 6.0	
					4.0 – 5.0	6.0 – 7.5	6.0 – 7.5			


### CYLINDRIQUE MOLETE /INOX

	Tête	Fût	M3	M4	M5	M6	M8	M10	M12
	Fine	Ouvert ou Borgne	0.7 - 1.5	0.7 – 3.0	0.7 – 3.3	0.7 – 3.3	0.7 – 3.3	0.8 – 1.5	0.8 – 1.5
			1.5 – 2.5	3.0 – 4.2	3.3 – 4.5	3.0 – 4.5	3.3 – 5.50	1.5 – 3.0	1.5 – 3.0
			2.3 – 3.2			4.5 – 6.0	4.5 – 6.0	3.0 – 4.5	3.0 – 4.5
							4.5 – 6.0	4.5 – 6.0	

#### Epaisseur à sertir mm

	Plate	Ouvert ou Borgne	0.7 – 1.5	0.7 – 3.0	0.7 – 3.3	0.7 – 3.3	0.7 – 3.3	0.8 – 1.5	0.8 – 1.5
			1.5 – 2.5	3.3 – 4.2	3.3 – 4.5	3.0 – 4.5	3.0 – 5.5	1.5 – 3.0	1.5 – 3.0
			2.3 – 3.2			4.5 – 6.0	4.5 – 6.0	3.0 – 4.5	3.0 – 4.5
								4.5 – 6.0	4.5 – 6.0

#### Epaisseur à sertir mm

	Fraisée	Ouvert ou Borgne	1.3 – 2.0	1.3 – 2.0	1.5 – 2.0	1.5 – 3.0	1.5 – 3.0	1.5 - 3.0	1.5 - 3.0
			2.0 – 3.0	2.0 – 3.0	2.0 – 3.0	3.0 – 4.0	3.0 – 4.0	3.0 – 4.5	3.0 – 4.5
				3.0 – 4.0	3.0 – 4.0	4.0 – 5.0	4.0 – 5.0	4.5 – 6.0	4.5 – 6.0
						5.0 – 6.0	5.0 – 6.0		

<b>ISO Métrique</b>	<b>M3</b>	<b>M4</b>	<b>M5</b>	<b>M6</b>	<b>M8</b>	<b>M10</b>	<b>M12</b>
<b>Ø de perçage</b>	5.0	6.0	7.0	9.0	11.0	13.0	16.0